



Dust extractor

X09603

DUSTOMAT DRY 2900



Technical data (Technical data and drawings may vary depending on the selected variant. Please refer to the type plate for the relevant values)

Mains voltage	400 V	Main filter surface	2 x 10 m ²
Nominal power	4.0 kW	Main filter quantity	2 pieces
Mains frequency	50 Hz	Collection volume	50 L
Nominal current	7.9 A	Dimensions (L x W x H)	1,030 x 845 x 2,170 mm
Circuit breaker	C16A	Weight	250 kg
Max. volume flow	2,900 m ³ /h	Type of cleaning	Manual rotation
Max. negative pressure	3,350 Pa	Compressed air consumption at 4-6bar	320l / min
Sound pressure level [at nominal speed]	[dBA] 74.8	Compressed air connection	2 x 3/4"
Intake opening	Ø 200 mm		

Application range

- » For the single or multi-station extraction
- » For dry, free-flowing dusts as well as for chips

Design

- » Collection volume: 50 L
- » Housing material and material of parts in contact with the medium: Steel (S235JR)
- » Installation location: EX zone-free

Options

- » Mobile and stationary design
- » Air recirculation operation and air extraction operation
- » With mechanical spark pre-separator
- » Filter type cartridge: PE, PTFE-Membran, PP (Oil / water repellent) optionally also in antistatic
- » With and without precoating
- » With post-filter: (H14) (Degree of separation >99,995%) or post-filter (F9)
- » With activated carbon filter to neutralise odours
- » With potential-free contact [On/Off] and [Fault message]: Operation / Fault function / Ready for operation / Filter dirty
- » Housing material: V2A
- » Material of parts in contact with the medium: V2A
- » ATEX marking: Dust inside II 3D Ex h IIC T140°C Dc X

Special Features

- » Particularly long filter life due to optimum ratio between air volume flow and filter surface as well as very effective filter cleaning.
- » High suction power ensures optimum extraction results at your collection point
- » Filter cleaning that is gentle on operating resources, thanks to the latest cleaning technologies
- » High separation efficiency of the filter media used ensures compliance with the required standards/directives.
- » The sound-insulated housing design and targeted air routing ensure low operating noise for quiet (continuous) operation.
- » Detachable/mobile dust collection container with large capacity ensures simple and quick removal or disposal of the separated material and reduces the number of disposal cycles. This minimises maintenance efforts as well as downtimes in the production process.

State of the art: This document was generated automatically. Technical changes reserved!