



Dust extractor DUSTOMAT_{DRY}

The new safety standard protecting you and your work force

The compact dust extractors of the DUSTOMAT DRY series are **suitable for almost all applications** thanks to their versatile configurations, including ATEX certification, HEPA filtration, and activated carbon options, effectively extract dusts that occur when processing a variety of materials including metal, plastic and composites (**separation efficiency of up to 99.995 %**).

Thanks to **air flow optimisation**, the filters of the DUSTOMAT DRY series have even higher energy efficiency compared to their predecessors. The **innovative filter cleaning system offers up to 50% saving in compressed air consumption**, coupled with an **extended filter service life**, means a significant reduction in ongoing running costs.



Your benefits

- » Configurable: performance, filter package, system structure
- » Powerful suction for optimal performance
- » Energy-efficient thanks to aerodynamically optimization
- » 50% reduction compressed air consumption thanks to innovative cleaning system
- » Low-noise system operation thanks to noise-optimized design
- » Recirculation or exhaust air operation options
- » Intuitive operation thanks to the convenient touch display
- » Simple disposal using a mobile dust collection drawer with liner
- » Compact design
- » Special designs (ATEX, H, activated carbon filter, etc.)



To the product



Technical Data

DUSTOMAT DRY		2000	2700	3300	3400	3500	4500	5800	6400
Max. volume flow	m³/h	2,000	2,700	3,100	3,400	3,500	4,500	5,800	6,400
Max. negative pressure	Pa	2,400	2,800	3,200	2,700	3,600	3,400	3,400	4,150
Intake opening	mm	160	180	200	250	200	250	315	315
Mains voltage	V	400	400	400	400	400	400	400	400
Nominal power	kW	2.2	3.0	4.0	3.0	5.5	4.0	5.5	5.5
Mains frequency	Hz	50	50	50	50	50	50	50	50
Nominal current	A	4,5	5,8	7,9	5,8	10,5	7,9	10,5	10,5
Circuit breaker	A	C16	C16	C16	C16	C16	C16	C32	C16
Compressed air connection	Inch	¼	¼	¼	¼	¼	¼	¼	¼
Main filter quantity	Pieces	2	2	2	2	2	4	4	4
Main filter surface	m²	2 × 5	2 × 5	2 × 10	2 × 10	2 × 10	4 × 10	4 × 16.7	4 × 16.7
Collection volume	l	50	50	50	90	50	90	90	90
Dimensions (L/W/H)	mm	1,600	1,600	1,600	2,120	1,600	2,120	2,120	2,120
		× 840	× 840	× 840	× 1,110	× 840	× 1,110	× 1,110	× 1,110
		× 1,440	× 1,440	× 1,680	× 1,930	× 1,680	× 1,930	× 2,170	× 2,170
Weight	kg	265	275	310	445	340	455	510	520
Sound pressure level	dB(A)	69	73.5	71.6	66.6	76.5	70	72	72.5
Order Number		X09700	X09701	X09702	X09704	X09703	X09705	X09707	X09706

Any questions?
Contact us!

ESTA Apparatebau GmbH & Co. KG
Gotenstraße 2 – 6
89250 Senden / Germany
Phone +49 7307 3409680-0
Fax +49 7307 804-500
E-Mail info@esta.com

www.esta.com

ESTA Extraction Technology

ESTA extraction technology has provided comprehensive solutions for all application areas for more than 50 years. From single devices for a wide range of application purposes to complex extraction systems – we ensure a clean working environment at all times. This protects machines, benefits your employees' health and lays the groundwork for efficient and quality-oriented working.

